

# Product information

SUN OIL COMPANY (Belgium) N.V.

Technical Customer Service

INGBERTHOEVEWEG 4 - B2630 AARTSELAAR - Tel: +323/458.12.30 - Fax: +323/458.14.78



## 2T Motosyn

**Description** Top quality two stroke engine lubricant, self mixing, based on synthetic esters. For use in two cycle engines operating under varying conditions as well as continuously high speeds and/or loads as these occur during racing happenings and sport riding.

**Application** In two cycle motorbikes and "carts", typical application rate being one part of lubricant for 50 parts of gasoline or as prescribed. Also suitable for injection two stroke engines. Specifically designed for use in high speed and more powerful two stroke engines.

**Specifications**

- 100 % synthetic ( ester based )
- Meets specifications " JASO FC "
- ISO GD
- PIAGGIO HEXAGON performance level

**Properties**

- Low smoke and fuel consumption reducing quality.
- Perfect lubrication and engine protection at all possible working temperatures and conditions.
- Excellent self-mixing properties in both leaded and lead-free gasoline, this in all applicable proportions.
- Maximum protection against wear and corrosion.

### Typical analysis :

- density at 15°C :	0,867
- viscosity at 40°C:	54 cSt
- viscosity at 100°C :	9.4 cSt
- flash point :	101°C
- pour point :	-48°C
- T.B.N. :	2.5 mg KOH/g