

Product information

SUN OIL COMPANY (Belgium) N.V.

Technical Customer Service

INGBERTHOEVEWEG 4 - B2630 AARTSELAAR - Tel: +323/458.12.30 - Fax: +323/458.14.78



Futura SAE 10W40

Description All season semi-synthetic turbo motor oil meeting the most severe conditions.

Application FUTURA is prescribed for all types of gasoline, LPG and diesel engines, turbo charged or naturally aspirated. In passenger cars and small commercial vehicles working under the severest heavy duty circumstances, in all seasons. Also everywhere below mentioned specifications are to be fulfilled.

Specifications

- API SL/CF
- Energy conserving (1.5 % EFEI -SEQ VI -API SH)
- ACEA A3 / B4
- MB 229.1
- VW 500.00 & VW 505.00
- BMW, PORSCHE, SAAB , SKODA.

Properties

- Excellent low temperature properties.
- Low volatility resulting in less oil consumption.
- Protection against wear, oxidation, formation of varnish and corrosion.
- Engines keep internally extremely clean.

Typical analysis :

density at 15°C	0.873
viscosity at 40°C / cSt	96
viscosity at 100°C / cSt	14.3
viscosity at -25°C / cP	6700
viscosity index	153
flash point °C	230
pour point °C	-30
TBN mg KOH/g	7.0
colour	L3.0